

Product datasheet CA®-Retentionfoil

1 Identification of the substance / preparation / company

Product details

Trade name: CA®-Retentionfoil

Application of the substance / Manufacture of dental pressure moulding

preparation: splints.

Manufacturer / Supplier: Scheu Dental GmbH

Am Burgberg 20 58642 Iserlohn

Germany

Tel. 0049 2374 9288-0

2 Composition / information on ingredients

Chemical characterization

CAS-Number: 261716-94-3 Designation: Copolyester

3 Handling and storage

Handling

Information for safe handling: When using do not eat, drink or smoke.

Provide suction extractors if dust is formed.

Storage

Storage conditions: Store dry and dark at max. 30°C

4 Physical, chemical, mechanical and biological properties

4.1 General properties

Properties	Guideline	Value	
Form	-	Solid	
Colour	-	Transparent	
Odour	-	Odourless	
Density	ISO 1183	1,17 g/cm ³	
Water absorption after 24 h at 23°C	ISO 62 Methode 1	-	



Product datasheet CA®-Retentionfoil

4.2 Mechanical properties

Properties	Guideline		Value	
Tensile strength	ISO 527		49 MPa	
Flectional strength	ISO 527		66 MPa no fracture 66 kJ/m²	
Impact strength 23°C	ISO 5256			
Notched 23°C	ISO 179			
Yield stress	ISO 527		45 MPa	
Yield strain	ISO 527		7%	
Elongation at tear	ISO 527		130%	
E-modulus	ISO 527		1624 MPa	
Hardness Shore D	DIN 53505		78	
Rockwell Hardness	ISO 2039-1	H358/30	115	

4.3 Thermal properties

Vicat softening point	ISO 306 Methode B	-	
Thermoform resistance	ISO 75 Methode A	92°C	
	ISO 75 Methode B	109°C	
Continuous stress temperature	ISO 75	-	

4.4 Biological properties / Biocompatibility

The material has been tested on biocompatibility according to DIN EN ISO 10993. It meets the requirements regarding biological compatibility for medical products / devices.

5 Stability and reactivity

Thermal decomposition / Conditions to avoid:

No decomposition by indended use.

6 Disposal

The material can be recycled after separation or deposed of like commercial or household waste.

The aforementioned data are given most conscientiously but without any obligation. Any processing details are provided merely for guidance: it is the user's responsibility to check the suitability of the product for the intended application.

Revision: 5 15/18	Hint: Valid from LOT 2116A to 3418A	Page 2 of 2
Replaced: 4 31/16	Time: Valid ITOM EOT ETTOA (O OTTOA	1 490 2 01 2